

Fluid Data Specifications

Model	Supra	Year	1992
--------------	-------	-------------	------

Model	Supra
Years Applied	1992
Engine	7M-GTE , 7M-GE
Transmission	

7M-GTE

	Capacity	Type
	L (US.qt , imp.qt.)	
A/C Refrigerant	600 ~ 700g (1.3 ~ 1.5 lb.)	R12 use R134a
Air condition Oil - Condenser	40 ~ 50cc (1.4 ~ 1.7 fl.oz.)	ND-Oil 6 use 8 , Suniso No.5GS (see TSB)
Air condition Oil - Receiver Drier	20cc (0.7 fl.oz.)	"
Air condition Oil - Evaporator	40 ~ 50cc (1.4 ~ 1.7 fl.oz.)	"
Air condition Oil - Pipes (3ft. or longer)	5cc (0.6 fl.oz.)	"
-		
Brakes	-	SAE J1703 DOT3
Clutch	-	SAE J1703 DOT3
Differential Oil	1.3L (1.4 , 1.1)	API GL-5 Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W-90 or 80W
-		

Engine Oil

Engine Oil Dry Fill	5.4L (5.7 , 4.8)	SG
Engine Oil w/Filter Change (Drain&Refill)	4.7L (5.0 , 4.1)	SG
Engine Oil w/oFilter Change (Drain&Refill)	4.4L (4.7 , 3.9)	SG
-		
Engine Cooling System w/ M/T	8.2L (8.7 , 7.2)	Ethylene glycol base (no alcohol)
Engine Cooling System w/ A/T	8.1L (8.6 , 7.1)	Ethylene glycol base (no alcohol)
-		
Fuel Tank	70L (18.5 gal. , 15.4 imp.gal.)	Unleaded OR87 (RON 91) or higher
-		
Power Steering	1,000cc (61.0 cu.in)	ATF Dexron II or III
-		

Transmission fluid

Automatic Transmission (Dry)	7.2L (7.6 , 6.3)	ATF Dexron II or III (see TSB)
Automatic Transmission (Drain&Refill)	1.6L (1.7 , 1.4)	ATF Dexron II or III (see TSB)
-		
Manual Transmission - R154	3.0L (3.2 , 2.6)	API GL-4 or GL-5 SAE 75W-90 or 80W-90

7M-GE

	Capacity	Type
	L (US.qt , imp.qt.)	
A/C Refrigerant	600 ~ 700g (1.3 ~ 1.5 lb.)	R12 use R134a

Air condition Oil - Condenser	40 ~ 50cc (1.4 ~ 1.7 fl.oz.)	Densooil 6 use 8 , Suniso No.5GS (see TSB)
Air condition Oil - Receiver Drier	20cc (0.7 fl.oz.)	"
Air condition Oil - Evaporator	40 ~ 50cc (1.4 ~ 1.7 fl.oz.)	"
Air condition Oil - Pipes (3ft. or longer)	5cc (0.6 fl.oz.)	"
-		
Brakes	-	SAE J1703 DOT3
Clutch	-	SAE J1703 DOT3
Differential Oil	1.3L (1.4 , 1.1)	API GL-5 Above -18°C (0°F) SAE 90 Below -18°C (0°F) SAE 80W-90 or 80W
-		
Engine Oil		
Engine Oil Dry Fill	4.9L (5.2 , 4.3)	SG
Engine Oil w/Filter Change (Drain&Refill)	4.4L (4.7 , 3.9)	SG
Engine Oil w/oFilter Change (Drain&Refill)	4.1L (4.3 , 3.6)	SG
-		
Engine Cooling System w/ M/T	8.1L (8.6 , 7.1)	Ethylene glycol base (no alcohol)
Engine Cooling System w/ A/T	8.0L (8.5 , 7.0)	Ethylene glycol base (no alcohol)
-		
Fuel Tank	70L (18.5 , 15.4)	Unleaded OR87 (RON 91) or higher
-		
Power Steering	1,000cc (61.0 cu in.)	ATF Dexron II or III
-		
Transmission fluid		
Automatic Transmission (Dry)	7.2L (7.6 , 6.3)	ATF Dexron II or III (see TSB)
Automatic Transmission (Drain&Refill)	1.6L (1.7 , 1.4)	ATF Dexron II or III (see TSB)
-		
Manual Transmission - W58	2.5L (2.6 , 2.2)	API GL-4 or GL-5 SAE 75W-90 or 80W-90